GTR-261X
Bi-Directional 1X9 Transceiver

Features

- Transmitter and receiver in one device
- SC/FC/ST receptacle bi-directional single fiber
- 1.25Gbps data rate
- A type: 1310nmFPTx/1550nmRx

  B type: 1550nmFP（DFB）Tx/1310nmRx laser transmitter
- Integrate WDM Filter, Isolation>30dB and Cross Talk<-40dB
- Class Ⅰ laser product compiles with IEC 60825-1
- 3.3V/ 5V power supply
- PECL/LVPECL signal input and output
- Operating Case Temperature

  Standard: 0℃~+70℃，
  Industrial:-40℃~+85℃

Applications

- SONET/SDH
- ATM
- Ethernet
- CCTV

Product Description

The GTR-261X optical transceiver is designed for use in 1.25Gbps data links. It provide the SC/FC/ST optical receptacle that is compatible with the industry standard connector. Both the transmitter and the receiver are packaged together with a top plastic cover and bottom shield. The transceiver operates with 3.3V/5V DC power supply.

Regulatory Compliance

Feature	Standard	Performance
Electrostatic Discharge (ESD) to the Electrical Pins	MIL-STD-883E Method 3015.7	Class 1(>500 V)
Electromagnetic Interference (EMI)	FCC Part 15 Class B	Compatible with standards
Laser Eye Safety	FDA 21CFR 1040.10 and 1040.11 EN60950, EN (IEC) 60825-1,2	Compatible with Class I laser product. Compatible with TÜV standards
Component Recognition	UL and CUL	UL file E317337
Green Products	RoHS	RoHS6

*Note: Products compliant with UL file E317337 use EOL9 series Part NO.

Absolute Maximum Ratings

Parameter	Symbol	Min.	Max.	Unit
Storage Temperature	TS	-40	+85	℃
Supply Voltage	VCC	-0.5	6.0	V
Operating Relative Humidity	-		95	%
Soldering Conditions Temp/Time			260/10	℃/s

Recommended Operating Conditions

Parameter	Symbol	Min.	Typical	Max.	Unit
Operating Case Temperature	TA	0		+70	ºC
		-40		+85	
Power Supply Voltage	VCC	4.75	5	5.25	V
Power Supply Current	ICC		60	100	mA
Data Rate			1.25		Gbps

Optical and Electrical Characteristic

Parameter		Symbol	Min.	Typical	Max.	Unit
Transmitter						
Centre Wavelength		λ C	1260	1310	1360	nm
			1480	1550	1580	
Spectral Width	FP	σ			4	nm
	DFB				1	

TYPE A Average Output Power	20Km	P0ut	-8		-3	dBm
	40Km		-3		+2	
TYPE B Average Output Power	20Km	P0ut	-10		-5	dBm
	40Km		-8		-3	
Extinction Ratio		EX	10			dB
Rise/Fall Time (20%---80%)		tr/tf			0.5	ns
Data Input Swing Differential		Vin	500		1600	mV
Input Differential Impedance		Zin	90	100	110	Ω
Input High Voltage		VH	VCC-1165		VCC-880	mV
Input Low Voltage		VL	VCC-1810		VCC-1475	mV
Eye Diagram		Compliant with ITU-T G.957				
Data Input		PECL/LVPECL				
Receiver						
Receiver Rate		1250				Mbps
Receiver Sensitivity		Pmin			-22	dBm
Receiver Overload		Pmax	-3			dBm
SD Assert		SDA			-24	dBm
SD De-Assert		SDD	-40			dBm
SD Hysteresis			0.5			dB
Output High Voltage		VH	VCC-1165		VCC-880	mV
Output Low Voltage		VL	VCC-1810		VCC-1475	mV
Data Output		PECL/LVPECL				

Pin Description

Pin	Name	Level	Description
1	VEER		Receiver Signal Ground, connect to receiver signal ground plane directly
2	RD+	LVPECL/PECL	Receiver Data Out, Terminate this pin with standard LVPECL/PECL techniques
3	RD-	LVPECL/PECL	Receiver Data Out, Terminate this pin with standard

			LVPECL/PECL techniques
4	SD	LVTTL/TTL	Signal Detect, LVTTL/TTL (Load resistor > 4.7KΩ)or LVPECL/PECL output, Normal optical input levels to the receiver result in a logic “1” output, asserted. Low input levels to the receiver result in a fault condition indicated by a logic “0”output, deasserted.
5	VccR		Receiver Power Supply ,provide +5V(+3.3V) a the recommended receiver power supply filter circuit. Locate the power filter circuit as close as possible to the VCCT pin
6	VccR		Transmitter Power Supply, provide +3.3V /+5V DC via the recommended transmitter power supply filter circuit. Locate the power filter circuit as close as possible to the VCCT pin
7	TD-	PECL	Transmitter Data in
8	TD+	PECL	Transmitter Data in
9	VEET		Transmitter Signal Ground, connect to the transmitter signal ground planed directly

Pin Definitions

Recommended Circuit

Notes:
1:Operating Voltage:+5V
R1=R3=R5=R7=82Ω
R2=R4=R6=R8=130Ω
2:Operating Voltage:+3.3V
R1=R3=R5=R7=130Ω
R2=R4=R6=R8=82Ω

DC COUPLING

1. For TTL SD Level, R1=R2=N.C., R7=100 ohm
2. For PECL SD Level, R1=130 ohm, R2=82 ohm, R7=100 ohm

AC COUPING

Package outline (unit: mm)

SC receptacle

FC receptacle

Ordering information

Part No.	Data Rate	Laser	Fiber Type	Distance	Optical Interface
GTR-2612(A)(B)(C)	1.25G	1310FP	SMF	20Km	SC/FC/ST
GTR-2613(A)(B)(C)		1550DFB		20Km	
GTR-2614(A)(B)(C)		1310 DFB		40Km	
GTR-2615(A)(B)(C)		1550DFB		40Km	

***A may be F, E, blank (F--FC, E--ST, blank--SC)**

***B may be I (I--- Industrial operating temperature)**

***C may be V, H, blank (V--3.3v, H--5V, blank--3.3v/5v)**

NOTICE:

Atech reserves the right to make changes to or discontinue any optical link product or service identified in this publication, without notice, in order to improve design and/or performance. Applications that are described herein for any of the optical link products are for illustrative purposes only. Atech makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

CONTACT:

Tel: (+86) 028-68229286

Fax: (+86) 028-87046097

E-mail: sales@atongcd.com

Website: http://cdaltx.en.alibaba.com